



UVIR Flame Detector Model X5200/X5200M/X5200G



DESCRIPTION



The X5200 UVIR Flame Detector meets the most stringent requirements worldwide with advanced detection capabilities and immunity to extraneous sources, combined with a superior mechanical design. The mounting arrangement allows the UV and IR sensors to monitor the same hazardous location with a 90 degree cone of vision. When both sensors simultaneously

detect the presence of a flame, an alarm signal is generated. The detector has Division and Zone explosion-proof ratings and is suitable for use in indoor and outdoor applications.

The standard output configuration includes fire, fault and auxiliary relays. An optional 0 to 20 mA output with HART can be provided in addition to the three relays. A model with pulse output is available for easy retrofitting into existing Det-Tronics controller based systems. Auxiliary relay and 0 to 20 mA output are not available with the pulse model. A tri-color LED on the detector faceplate indicates normal condition and notifies personnel of fire alarm or fault conditions.

The X5200M UV/IR detector utilizes a molybdenum (moly) UV sensing element. Moly-based UV sensors have an increased spectral range of 1850 to 2650 angstroms, which is better suited for detecting substances with unusual chemistry and some black powders.

The X5200 housing is available in aluminum or stainless steel, with NEMA 4X and IP66/IP67 rating.

Typical applications include:

- Munitions
- Petrochemical applications
- Turbines
- Refineries

HIGHLIGHTS

- ▲ Complies with FM 3260
- ▲ EN54 certified
- ▲ Certified SIL 2 capable
- ▲ ATEX Directive compliant
- ▲ EQP models available
- ▲ A new level of false alarm rejection
- ▲ Responds to a fire in the presence of modulated blackbody radiation (i.e. heaters, ovens, turbines) without false alarm
- ▲ HART models available
- ▲ FDT/DTM capable
- ▲ High speed capability
- ▲ Microprocessor controlled heated optics for increased resistance to moisture and ice
- ▲ Automatic, manual or magnetic oi® (optical integrity) testing — no external test lamp required
- ▲ Easily replaceable oi plate
- ▲ Fire, fault and auxiliary relays standard
- ▲ MODBUS RS-485 communication
- ▲ 0 to 20 mA isolated output (optional)
- ▲ Pulse output for compatibility with controller based systems (optional)
- ▲ A tri-color LED on the detector faceplate indicates normal condition and notifies personnel of fire alarm or fault conditions
- ▲ Mounting arm allows easy sighting
- ▲ Integral wiring compartment for ease of installation
- ▲ Class A wiring per NFPA-72
- ▲ Meets NFPA-33 response requirement for under 0.5 second (available when model selected)
- ▲ RFI and EMC Directive compliant
- ▲ Built-in data logging / event monitoring

SPECIFICATIONS

Operating Voltage	24 Vdc. Operating range is 18 to 30 Vdc Maximum ripple is 2 volts peak-to-peak
Power Consumption	2.8 watts @ 24 Vdc nominal 17.5 watts @ 30 Vdc with EOL resistor installed and heater on maximum
Relays	Contacts rated 5 amperes at 30 Vdc <u>Fire Alarm:</u> — Form C (NO and NC contacts) — normally de-energized — latching/non-latching <u>Fault:</u> — Form A (NO contacts) — normally energized — latching/non-latching <u>Auxiliary*:</u> — Form C (NO and NC contacts) — normally energized — latching/non-latching
Current Output* (Optional)	0–20 mA (± 0.3 mA), with a maximum loop resistance of 500 ohms from 18–19.9 Vdc 600 ohms from 20–30 Vdc
Temperature Range	<u>Operating:</u> —40°F to +167°F (–40°C to +75°C) <u>Storage:</u> —67°F to +185°F (–55°C to +85°C) Hazardous location ratings from –55°C to +75°C available on flameproof model
Humidity Range	0 to 95% relative humidity, can withstand 100% condensing humidity for short periods of time
Spectral Sensitivity Range	All X5200 IR wavelength range 4-5 microns. X5200/ X5200G UV wavelength range 185-245 nanometers X5200M UV wavelength range 185-265 nanometers
Field of View	The detector has a 90 degree cone of vision (horizontal) with the highest sensitivity lying along its central axis
Source Tube	Contains radioactive isotope Krypton 85 (Kr ⁸⁵) Calculated Activity: 14,800 Becquerels (0.4µCi) Note: Not applicable to model X5200G
Warranty	3 years
Enclosure Material	Copper-free aluminum (painted) or stainless steel (316/CF8M Cast)
Conduit Entry Size	3/4 inch NPT or M25.
Shipping Weight (Approximate)	<u>Aluminum:</u> 7 lbs. (3.2 kg) <u>Stainless Steel:</u> 14.6 lbs. (6.7 kg)
Wiring	16 AWG or 2.5 mm ² shielded cable is recommended

Response Characteristics

Very High Sensitivity UV & IR, Low Arc, TDSA On, Quick Fire On

Fuel	Size	Distance Feet (m)	Typical Response Time (seconds)
n-Heptane	1 x 1 foot	85 (25.9)	14
Methane	32 inch plume	65 (19.8)	5

NOTE: Refer to the X5200 instruction manual 95-8546 for details regarding detector response.

*Auxiliary relay and 0 to 20 mA output are not available on pulse output model.

Certification



Class I, Div. 1, Groups B, C & D (T5)
Class II, Div. 1, Groups E, F & G (T5)
Class I, Div. 2, Groups A, B, C & D (T3)
Class II, Div. 2, Groups F & G (T3)
Class III.
Enclosure NEMA/Type 4X per NEMA 250

For FM Zone approval information, refer to the X5200 instruction manual (95-8546)



IEC 61508

Certified SIL 2 Capable
Applies to specific models –
Refer to the SIL 2 Certified
X5200 Safety Manual (95-8672)



VNIIFTRI

Certificate of Conformity to TP TC 012/2011
TC RU C-US. BH02.B.00234

2ExdellCT6/T5 IP66
T6 (Tamb = –55°C to +60°C)
T5 (Tamb = –55°C to +75°C)
– OR –

1ExdIICT6/T5 IP66
T6 (Tamb = –55°C to +60°C)
T5 (Tamb = –55°C to +75°C)



VNIPO

Certificate of Conformity to technical regulations, GOST R 53325-2012
C-US. ПБ01.B.02841



Approvals to EN54-10
See X5200 instruction manual (95-8546) for details



DEMKO 01 ATEX 132195X Increased Safety Model

CE 0539 Ex II 2 G II 2 D

Ex db eb IIC T6...T5 Gb
Ex tb IIIC T85°C Db
T6 (Tamb –50°C to +60°C)
T5 (Tamb –50°C to +75°C)
IP66/IP67

Flameproof Model

CE 0539 Ex II 2 G II 2 D

Ex db IIC T6...T5 Gb
Ex tb IIIC T85°C Db
T6 (Tamb –55°C to +60°C)
T5 (Tamb –55°C to +75°C)
IP66/IP67



IECEx Certificate of Conformity

IECEx ULD 06.0018X
Ex db eb IIC T6...T5 Gb
Ex tb IIIC T85°C Db
T6 (Tamb = –50°C to +60°C)
T5 (Tamb = –50°C to +75°C)
IP66/IP67
– OR –

Ex db IIC T6...T5 Gb
Ex tb IIIC T85°C Db
T6 (Tamb = –55°C to +60°C)
T5 (Tamb = –55°C to +75°C)
IP66/IP67



UL-BR 17.0216X

Ex db eb IIC T6...T5 Gb
Ex tb IIIC T85°C Db
T6 (Tamb -50°C TO +60°C)
T5 (Tamb -50°C TO +75°C)
IP66/IP67
- OR -

Ex db IIC T6...T5 Gb
Ex tb IIIC T85°C Db
T6 (Tamb -55°C TO +60°C)
T5 (Tamb -55°C TO +75°C)
IP66/IP67

Specifications subject to change without notice.

All trademarks are the property of their respective owners. ©2020 Carrier. All Rights Reserved.

Det-Tronics manufacturing system is certified to ISO 9001—the world's most recognized quality management standard.



Corporate Office
6901 West 110th Street
Minneapolis, MN 55438 USA
www.det-tronics.com

Phone: +1 952.941.5665
Toll-free: +1 800.765.3473
Fax: 952.829.8750
det-tronics@carrier.com

